

SAUSHED 600™

Designed for
zero
maintenance

Flexible, allowing print:
in **any orientation**



High resolution coding

2–18mm print height
Up to 8 lines of text

2 mm
18 mm

High Resolution Coding & Marking

1 to 8 lines of print, with 2-18mm print height.



Touch Controller

Simple interactive windows programming with Sauven **Pro** software.

JPEG
BMP

Graphics, Logos & Barcodes

Easily import JPEG & BMP graphics using Sauven **Pro** software.



PC Connectivity

via USB cable or Ethernet for direct message creation or factory network system.



Stand Alone Printer

Use a USB stick to transfer print messages from Sauven **Pro** software.



1D & 2D Barcodes

High resolution printing of multiple barcode variants.



Out of the Box Installation

With minimal components for maximum reliability.



Multi Port Connection

For encoders, external alarms and alternative product detection devices.

ABC
DEF

True Type Font & Unicode

Enables message creation in any font and in any language.



Simple Screen & Keyboard

For local control of printer speed and printer direction, message selection and message delay.

AA

Ink Saver Mode

Reduce ink consumption by up to 50%.



Large Solvent Based Ink Cartridge

Low cost coding and clean inking system, ideal for printing on to porous and non-porous surfaces.

Included

Sauven **Pro6** software™

- Simple interactive Windows programming
- Unlimited message storage
- Ink saver print mode
- Uses True Type font & Unicode
- Imports JPEG & BMP logos
- Multi language support

TOUCH™ controller

Control your printer
with just a Touch

Programming
without training



Smart thinking: Smart printing

SAUSHED 
SMART THINKING: SMART PRINTING



Specification

Features

- Prints in any orientation
- 1 to 8 lines of print
- 2mm - 18mm total print height
- High resolution piezo print head
- Prints text, graphics, logos and barcodes
- Prints time and multiple date formats
- Continuous repeat print capability
- 100m/min print speed (50m/min for barcodes and 2mm text)
- Single start /stop print button
- Visual alarm indicator including ink low
- Message width, delay and print direction control
- Message selection
- Product detection photocell
- Weight 1.7kg (excluding ink cartridge and brackets)
- Size 242 x 178 x 90mm

Connectivity

- RS232 and RS485 for Sauven Touch controller
- USB-A memory stick included
- USB-B for cable connection
- Ethernet (optional)
- I/O port for encoder, alarm beacon and external photocells

Ink

- Sealed replaceable ink cartridge (up to 15 million characters)
- Oil based inks for porous surfaces
- Solvent based inks for non-porous surfaces
- UV inks for instant LED curing
- Various colours

Electrical

- 90-260VAC to 24VDC power supply included

TOUCHTM controller

Features

- 7" Touch Screen
- Simple interactive windows programming
- Uses Sauven Pro software

Connectivity

- USB-A, USB-B, RS232, RS485 Multi port, Ethernet (Optional)
- 24 v DC input
- Support external alarms, beacons, encoders
- Auto programming with barcode reader

Sauven **Pro6** softwareTM

Features

- Compatible with Windows XP and above
- Intuitive icon led message creation
- True Type Font and Unicode supported

- Graphics, logos & barcodes directly imported in JPEG and BMP format
- Time and multiple date formats
- Ink saver print mode
- Unlimited message storage
- Multi language support

*Sauven Marking Ltd continuously improves products and software.
Specifications are subject to change.*

www.saushed.com



Saushed Worldwide

Saushed ink jet printers are available through a global network of qualified distributors offering a total sales and support service.